

ALABAMA ASPHALT PAVEMENT ASSOCIATION



ALABAMA ASPHALT PAVEMENT ASSOCIATION

Alabama Asphalt Pavement Association

630 Adams Avenue

Montgomery, AL 36104

334/834/5314 (Phone) 334/834/5537 (Fax)

E-mail: alapa@bellsouth.net

Web site: www.alasphalt.com

ADVANTAGE OF THIN LIFT HMA OVERLAYS

DECEMBER 4, 2024

68TH ANNUAL KANSAS
ASPHALT PAVING
CONFERENCE

Agency Funding

- ▣ ALDOT Funds Are Limited Even With Gas Tax Increase.
- ▣ ALDOT New Construction Projects Are Still Uncommon.
- ▣ If You Can Not Afford To Maintain Existing System, Why Add New To System?
- ▣ ALDOT Priority Is Maintaining Current System.
- ▣ Need To Determine Best Pavement Preservation Treatments To Maintain System.

What Does Public Want In Roads?

What Does Public Want In Roads?

- ▣ Smoothness
- ▣ Safety


Objectives -

- ▣ **Why** Thin Lift Asphalt?
- ▣ **Where** Thin Lift Asphalt?
- ▣ **Specifications** For Thin Lift Asphalt.
- ▣ **History** Of Thin Lift Asphalt.
- ▣ **Economics** Of Thin Lift Asphalt.

Why Thin Lift Asphalt?


Why Thin Lift Asphalt?

- ▣ Funding Crisis
 - Escalating Construction Cost
 - Limited Revenue



Why Thin Lift Asphalt?

▣ Concept Of Pavement Preservation



Why Thin Lift Asphalt?

Benefits To The Traveling Public

- Improved Ride
- Improved Smoothness
- Public Perception – Freshly Paved Road – New Road
- Public Perception – No Broken Windshields
- Local / In State Contractors – Contributing To Tax Base And Employment At Local / State Level
- Increased Competition
- Future Value Of RAP
- Adding Structural Capacity To Pavement
- Building Perpetual Pavement 1” At The Time

Pavement Preservation Comparisons

	Thin Lift	Micro-Surface	Scrub Seal	Chip Seal
Corrects Surface Distress	√	√	√	√
Increase Skid Resistance	√	√	√	√
Minimizes Curb Loss	√	√	√	√
Can Be Applied In One Pass	√	√	√	√
Eliminates Loose Aggregate	√	√		
Corrects Minor Rutting	√			
Minimizes Delamination	√			
Improves Ride Quality	√			
Increases Structural Strength	√			
Improves Pavement Drainage And Pavement Cross Slope	√			

Where Thin Lift Asphalt?

Where Thin Lift Asphalt?

- ▣ Roads That Are Structurally Sound



Good Candidates?

Good Candidate?



Good Candidate?



Good Candidate?



Good Candidate?



Specifications For 3/8" Thin Lift Asphalt

Alabama DOT Specifications

3/8 Inch Maximum Aggregate Size Mix

- ▣ SuperPave Mix
- ▣ ALDOT Uses Maximum Aggregate Size Mixes



3/8 Inch Maximum Aggregate Size Mix

Sieve Size	3/8 Inch Mix, Section 424
1/2"	100
3/8"	95 - 100
#4	75 - 100
#16	30 - 60
#200	6 - 12

3/8 Inch Maximum Aggregate Size Mix - Design Considerations

Fine Aggregate Angularity (FAA) Requirements (Section 424 Mixes)

- ▣ FAA Greater Than Or Equal To 43 For Less Than 1 Million 20 Year Design ESALs (ESAL Range A/B Mixes).
- ▣ FAA Greater Than Or Equal To 45 For Between 1 Million And 30 Million 20 Year Design ESALs (ESAL Range C/D And ESAL Range E Mixes).

Carbonate Stone (Limestone) Requirements (Section 424 Mixes)

- ▣ Varies From A Maximum of 30% To A Maximum of 50% Depending Upon BPN 9 Value of Aggregate Source.

Liquid Asphalt Binder Requirements (Section 424 Mixes)

- ▣ PG 67-22 Required For Less Than 10 Million 20 Year Design ESALs (ESAL Range A/B And ESAL Range C/D Mixes).
- ▣ PG 76-22 Required For Between 10 Million And 30 Million 20 Year Design ESALs (ESAL Range E Mixes).

Design Gyration And Minimum Design AC Requirements (Section 424 Mixes)

- ▣ Design Gyration Of 60 Gyration.
- ▣ Minimum Design AC Content Of 5.90%.

Air Voids, VMA, Dust Proportion And TSR Requirements (Section 424 Mixes)

- ▣ Design Air Voids Of 4.0%.
- ▣ Minimum Design VMA Of 16.5% And Maximum Design VMA Of 18.0% With A 0.5% Production VMA Tolerance.
- ▣ Dust Proportion Range of 0.90 To 2.00 Based On Effective Asphalt Content.
- ▣ TSR Of Minimum Of 0.80.

RAP And RAS Requirements And Warm Mix (Section 424 Mixes)

- ▣ Maximum 20% RAP Use.
- ▣ No RAS Use.
- ▣ Warm Mix Asphalt Allowed As Contractor Option On All Section 424 Mixes.

Spread Rate And Density Requirements (Section 424 Mixes)

- ▣ Spread Rate Can Be Specified From A Minimum of 80 Pounds Per Square Yard (0.72 Inches) To A Maximum Of 110 Pounds Per Square Yard (0.99 Inches).
- ▣ Density Requirement Is To Satisfaction Of Engineer. Typically, A Roller Pattern Using Non-Destructive Density Gauges.

3/8 Inch Maximum Aggregate Size Mix (Section 424 Mix)

Sample Mix Design (Contractor)

- ▣ 30% 1/4" Limestone Chips.
- ▣ 26% # 89 Granite.
- ▣ 15% Manufactured Granite Sand.
- ▣ 8% Sand.
- ▣ 20% RAP.
- ▣ 1% Baghouse Fines.
- ▣ Design Asphalt Content : 5.90%.

3/8" Asphalt Mix (Section 424 Mix)

Sieve Size	3/8 Inch Mix % Passing	Contractor JMF % Passing
1/2"	100	100
3/8"	95 - 100	97
#4	75 - 100	78
#16	30 - 60	33
#200	6 - 12	6.7

History Of Thin Lift Asphalt

ALDOT's First 3/8" Asphalt Mix Project

- ▣ Approximately 2002.
- ▣ SR 135 – Baldwin County.
- ▣ Contractor – H.O. Weaver & Sons, Inc.
- ▣ Excellent Performance For 10 Plus Years.



CR551





INGERSOLL-RAND











3/8" Mix Projects

Project Details – Thin Lift 3/8” Asphalt

- ▣ Project Letting Date – April 7, 2017.
- ▣ Project Length – 14.599 Miles In Butler County.
- ▣ Bituminous E Treatment To Address Cracking In Existing Roadway.
- ▣ Thin Lift HMA – 90 Pounds Per Square Yard of 3/8” Maximum Aggregate Size Mix.
- ▣ ALDOT Guidelines Allow Placement Rate From Minimum Of 80 Pounds Per Square Yard To Maximum Of 110 Pounds Per Square Yard.
- ▣ Project Construction – Summer 2017.

3/8 Inch Maximum Aggregate Size Mix Design

- ▣ 24% Coarse Sand
- ▣ 21% Granite Screenings
- ▣ 20% RAP
- ▣ 13% Crushed Gravel
- ▣ 11% Shot Gravel
- ▣ 10% #8910 Limestone
- ▣ 1% Baghouse Fines
- ▣ Design Asphalt Content : 5.90% (PG 67-22)
- ▣ 60 Design Gyration

Thin Lift Asphalt Edge Line



Thin Lift Asphalt Longitudinal Joint



Thin Lift Asphalt Texture



Ride Quality / Smoothness

- ▣ ALDOT Uses Inertial Profiler To Measure Smoothness.
- ▣ ALDOT Measures Smoothness By Mean Roughness Index (MRI).
- ▣ Lower MRI = Smoother Ride

Ride Quality / Smoothness - Thin Lift Asphalt

- ▣ Average Pre - Construction MRI (2017) = 88.9 Inches Per Mile.
- ▣ Average Post - Construction MRI (2017) = 36.8 Inches Per Mile.
- ▣ Significant Average MRI Improvement Of 52.1 Inches Per Mile.
- ▣ Average Post - Construction MRI (2022) = 50 Inches Per Mile.
- ▣ Smooth Quiet Ride.

Project Cost – Thin Lift Asphalt

- ▣ Bituminous Treatment E – 225,000 Square Yards At \$1.25 Per Square Yard.
- ▣ Thin Lift Asphalt – 10,200 Tons At \$80.20 Per Ton. Approximately \$3.61 Per Square Yard.
- ▣ Total Cost - \$1,099,290.
- ▣ Average Cost Per Mile = \$75,299 Per Mile.
- ▣ Average Cost Per Lane Mile = \$37,649 Per Lane Mile.

Thin Lift Asphalt (One Year Old)



Thin Lift Asphalt (7 Years Old)



3/8" Mix Projects

Project Details – 3/8” Asphalt Mix

- ▣ Project Letting Date – January 31, 2020.
- ▣ Project Length And Description – 3.587 Miles On US 231 From Ross Clark Circle In Dothan To The Dale County Line.
- ▣ Prime Contractor – Midsouth Paving, Inc.
- ▣ 0.75” Micro Milling And Overlay Of Existing Roadway.
- ▣ 3/8” Mix HMA – 90 Pounds Per Square Yard (0.81 Inches) of Section 424 ESAL Range E Mix.
- ▣ ALDOT Guidelines Allow Placement Rate From Minimum Of 80 Pounds Per Square Yard (0.72 Inches) To Maximum Of 110 Pounds Per Square Yard (1.00 Inches).
- ▣ Project Construction – Summer 2020.

3/8" Asphalt Mix

Project Mix Design

- ▣ 20% #8910 Limestone.
- ▣ 20% #8910 Granite Screenings.
- ▣ 20% Sand.
- ▣ 20% RAP.
- ▣ 12% Shot Gravel.
- ▣ 8% #89 Limestone.
- ▣ Design Asphalt Content : 5.90%.

3/8" Asphalt Mix

Sieve Size	3/8 Inch Mix % Passing	Project JMF % Passing
1/2"	100	100
3/8"	95 - 100	99
#4	75 - 100	86
#16	30 - 60	49
#200	6 - 12	7.1

Ride Quality / Smoothness

- ▣ ALDOT Uses Inertial Profiler To Measure Smoothness.
- ▣ ALDOT Measures Smoothness By Mean Roughness Index (MRI).
- ▣ Lower MRI = Smoother Ride

Ride Quality / Smoothness – 3/8” Asphalt

- ▣ Average Pre – Construction MRI (2019) = 83.4 Inches Per Mile.
- ▣ Construction Build Up – 0.75” Micro Milling And 90 Pounds Per Square Yard HMA (Approximately 0.81”)
- ▣ Average Post – Construction MRI (2021) = 55.3 Inches Per Mile.
- ▣ Significant Average MRI Improvement Of 28 Inches Per Mile.
- ▣ Average Post – Construction MRI (2023) = 58 Inches Per Mile
- ▣ Smooth Quiet Ride.

Project Cost – 3/8”Asphalt Mix

- ▣ 3/8” Asphalt – 7,035 Tons At \$102.85 Per Ton.
Approximately \$4.63 Per Square Yard.
- ▣ Total Cost - \$723,549.75.
- ▣ Average Cost Per Mile = \$201,714.45 Per Mile.
- ▣ Average Cost Per Lane Mile = \$33,619.075 Per Lane Mile.

3/8" Mix Projects

City Of Opelika Road







Performance To Date

- ▣ No Structural Failures Reported.
- ▣ No Major Performance Issues Reported.
- ▣ No Friction Number Issues Reported.

Economics Of Thin Lift Asphalt

ECONOMICS OF PREVENTIVE MAINTENANCE TREATMENTS



Pavement Preservation Comparisons

	Thin Lift	Micro-Surface	Scrub Seal	Chip Seal
Corrects Surface Distress	√	√	√	√
Increase Skid Resistance	√	√	√	√
Minimizes Curb Loss	√	√	√	√
Can Be Applied In One Pass	√	√	√	√
Eliminates Loose Aggregate	√	√		
Corrects Minor Rutting	√			
Minimizes Delamination	√			
Improves Ride Quality	√			
Increases Structural Strength	√			
Improves Pavement Drainage And Pavement Cross Slope	√			

Other Considerations

- ▣ Economic Benefit Of In State Contractors Versus Out Of State Contractors.
- ▣ Local / In State Contractors – Contribute To Tax Base And Employment At Local / State Level.
- ▣ Increased Competition.
- ▣ Future Value Of RAP.


Cost Data Background

- ▣ Cost Data Obtained From ALDOT Bid History And Averaged For Discussion.
- ▣ Thin Lift Asphalt – 2023 Statewide Average For 3/8” Mix.
- ▣ Micro Surfacing – 2023 Average From 18 Projects.
- ▣ Triple Layer Bituminous Surface Treatment – 2022 Average From 2 Projects.
- ▣ Scrub Seal – 2023 Average From 28 Projects.

Cost Comparison (Initial Cost)

- ▣ Micro Surfacing = \$3.05 Per Square Yard
- ▣ Scrub Seal = \$3.25 Per Square Yard
- ▣ Thin Lift HMA = \$4.48 Per Square Yard
- ▣ Triple Layer Bituminous Treatment = \$5.20 Per Square Yard
- ▣ Scrub Seal And Micro Surfacing (Cape Seal) = \$6.30 Per Square Yard

Cost Comparison (Initial Cost)



Performance Life Definition

- ▣ Length Of Time Pavement Treatment Lasts Before Exhibiting Distresses Generally Equivalent To Condition of Original Pavement.
- ▣ $\text{Treated Distress} / \text{Untreated Distress} = 50\% - 100\%$.
- ▣ Pavement Treatment May Remain In Service Well Past End Of Performance Life.

Performance Life Background

- ▣ Estimates Of Performance Life Taken From Average Of Numerous Sources Including Data From ALDOT, CDOT, MDOT, MNDOT, ODOT, FHWA, NCPP and NCAT.
- ▣ Performance Life Dependent Upon Many Things Including Pre-Existing Condition Of Road, Traffic Levels, Etc.
- ▣ Current Studies By NCAT To Further Detail This Issue.

NCAT Preservation Research - NCAT Test Track, US 280, Lee County Road 159



NCAT Preservation/Maintenance

www.NCAT.us

... [Close] [Check]


Treatment

- Single layer chip seal ✓
- Rejuvenating fog seal
- FiberMat chip seal

Condition **Time**


- Fair ✓ 0.0
- Good 0.5
- Poor 1.0

MAIN PAN... **Treatments Location (Google Maps)**



Time to Poor (Control) Crack Reduction (Average) Time to Poor (Treatment)


0.9 **34.4** **8.5**




Overall Section Condition

FAIR


Cracking % of Area



Rutting (mm)



IRI (in/mile)



NCAT Preservation/Maintenance

www.NCAT.us

... [Close] [Check]

Search Treatment

- Cape seal
- Single layer micro surfacing** ✓
- Single layer micro surfacing with crack sealing


Search Condition

- Fair** ✓
- Good
- Poor


Search Time

- 0.0
- 0.5
- 1.0

MAIN PAN... Treatments Location (Google Maps)




Time to Poor (Control)	Crack Reduction (Average)	Time to Poor (Treatment)
1.0	26.3	6.5



Overall Section Condition

FAIR


Cracking % of Area



Rutting (mm)



IRI (in/mile)



NCAT Preservation/Maintenance

www.NCAT.us

... [Close] [Check]


Treatment

- Virgin thinlay with PG67-22 ✓
- Virgin thinlay with PG67-22 on 100% foamed re...
- Virgin thinlay with PG76-22

Condition **Time**


- Fair ✓ 0.0
- Good 0.5
- Poor 1.0

MAIN PAN... **Treatments Location (Google Maps)**



Time to Poor (Control) Crack Reduction (Average) Time to Poor (Treatment)


1.1 **30.3** **6.5**



Overall Section Condition

FAIR


Cracking % of Area



Rutting (mm)



IRI (in/mile)



NCAT Preservation/Maintenance

www.NCAT.us

... [Close] [Check]

Treatment

- Double layer micro surfacing ✓
- FiberMat Cape seal


Condition **Time**

Fair ✓	0.0
Good	0.5
Poor	1.0

MAIN PAN... **Treatments Location (Google Maps)**




Time to Poor (Control)	Crack Reduction (Average)	Time to Poor (Treatment)
1.2	32.3	6.5



Overall Section Condition

FAIR


Cracking % of Area



Rutting (mm)




IRI (in/mile)



Performance Life Estimates

- ▣ Thin Lift HMA = 10 Years
- ▣ Scrub Seal And Micro Surfacing (Cape Seal) = 6 Years
- ▣ Scrub Seal = 5 Years
- ▣ Triple Layer Bituminous Surface Treatment = 5 Years
- ▣ Micro Surfacing = 4 Years


Performance Life Estimates



Life Cycle Cost Comparison (Annualized Cost) (No Discount Rate)

- ▣ Thin Lift HMA = \$0.45 Per Square Yard
- ▣ Scrub Seal = \$0.65 Per Square Yard
- ▣ Micro Surfacing = \$0.76 Per Square Yard
- ▣ Triple Layer Bituminous Surface Treatment = \$1.04 Per Square Yard
- ▣ Scrub Seal And Micro Surfacing (Cape Seal) = \$1.05 Per Square Yard

Life Cycle Cost Comparison (Annualized Cost)



Thank You

- ▣ ALDOT (Scott George, John Jennings And Frank Bell).

Questions ?????



Questions ?????



Questions ?????



Questions ?????



ALABAMA ASPHALT PAVEMENT ASSOCIATION



ALABAMA ASPHALT PAVEMENT ASSOCIATION

Alabama Asphalt Pavement Association

630 Adams Avenue

Montgomery, AL 36104

334/834/5314 (Phone) 334/834/5537 (Fax)

E-mail: alapa@bellsouth.net

Web site: www.alasphalt.com